

HAZARDOUS SUBSTANCES RISK ASSESSMENT

Designer Contracts Ltd

Unit 8, Church View, Coney Green, Chesterfield, S45 9HA

CPL - Stopgap P121 Acrylic Primer (Fball)	Date of Assessment : 03/06/2024	Reference : CPL - Stopgap 121 Acrylic Primer (Fball)
Risk Assessor : Laura Cross	Risk Assessor :	
Other People Involved in Making This Assessment : Antony Maidens		

R or H Descriptors:	S or P Descriptors:
Additional Information	
Workspace Exposure Limit (WEL) No WEL stated on SDS	

Primary route(s) of entry : Absorption, Ingestion, Inhalation	
This is a Group Substance.	The quantity used per batch or work period is: Medium (1-1000kg or 1-1000L)
The Substance is a Liquid of Low volatility	
is the control measure appropriate to control the health risks from the use of this substance. Health Surveillance is not required.	

Existing Control Measures
1. Always use in a well ventilated area.
2. First aid measures: Inhalation This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.
3. By inhalation: This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.
4. By skin contact: This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or if necessary shower the affected person thoroughly with cold water and neutral soap.
5. By eye contact: Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage.
6. By ingestion/aspiration: Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.
7. Suitable extinguishing media Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder),
8. Unsuitable extinguishing media: Non-applicable

9. ACCIDENTAL RELEASE MEASURES For non-emergency personnel: Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product
10. Evacuate the area and keep out those who do not have protection. For emergency responders: Wear protective equipment. Keep unprotected persons away
11. Environmental precautions: It is recommended to avoid environmental spillage of both the product and its container. cleaning up: It is recommended: Absorb the spillage use sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents.
12. General occupational hygiene Do not eat or drink during the process, washing hands afterwards with suitable cleaning products. Technical recommendations to prevent environmental risks It is recommended to have absorbent material available at close proximity to the product
13. Technical measures for storage Minimum Temp.: 5 °C Maximum Temp.: 30 °C Maximum time: 6 Months General conditions for storage Avoid sources of heat, radiation, static electricity and contact with food
14. Respiratory protection The use of protection equipment (FFP3 Masks) will be necessary if a mist forms or if the occupational exposure limits are exceeded
15. Mandatory hand protection Protective gloves against minor risks Replace gloves in case of any sign of damage. prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+ A1:2010 and EN ISO 374-1:2016+A1:2018
16. Mandatory face protection Panoramic glasses against splash/projections. EN 166:2002 EN ISO 4007:2018 Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.
17. Additional emergency measures Emergency shower ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011 Eyewash stations DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
18. It is not possible to assign a specific code, as it depends on the intended use by the user Waste class (Regulation (EU) No 1357/2014) Non dangerous
19. Return all empty containers back to region to be disposed of in Drum B

Documents Associated with this Risk Assessment : Stopgap-P121-iss-8.pdf(SDS) Stopgap 121 Acrylic Primer FBall.pdf(SDS)

Review Date : 07/06/2025