

HAZARDOUS SUBSTANCES RISK ASSESSMENT

Designer Contracts Ltd

Unit 8, Church View, Coney Green, Chesterfield, S45 9HA

CPL - Styccobond F48 Plus	Date of Assessment : 06/06/2024	Reference : CPL - Styccobond F48 Plus
Risk Assessor : Laura Cross	Risk Assessor :	
Other People Involved in Making This Assessment : Antony Maidens		

R or H Descriptors:	S or P Descriptors:
Additional Information	
Workspace Exposure Limit (WEL) No WEL stated on Safety Data Sheet	

Primary route(s) of entry : Absorption, Ingestion, Inhalation	
This is a Group Substance.	The quantity used per batch or work period is: Medium (1-1000kg or 1-1000L)
The Substance is a Liquid of Low volatility	
is the control measure appropriate to control the health risks from the use of this substance. Health Surveillance is not required.	

Existing Control Measures
1. Always use in a well ventilated area.
2. Description of first aid measures. By inhalation: This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest.
3. Request medical attention if symptoms persist.
4. By skin contact: This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or if necessary shower the affected person thoroughly with cold water and neutral soap.
5. By eye contact: Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage.
6. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.
7. By ingestion/aspiration: Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.
8. Suitable extinguishing media: Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder),
9. Unsuitable extinguishing media: Non-applicable

10. ACCIDENTAL RELEASE MEASURES Personal precautions, protective equipment and emergency procedures:For non-emergency personnel:
11. Personal protection equipment must be used against potential contact with the spilt product Evacuate the area and keep out those who do not have protection.
12. For emergency responders: Wear protective equipment. Keep unprotected persons away
13. Environmental precautions: Avoid spillage into the aquatic environment as it contains substances potentially dangerous for this.
14. Contain the product absorbed in hermetically sealed containers. In the case of serious spillage into the aquatic environment notify the relevant authority.
15. Methods and material for containment and cleaning up: It is recommended: Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents.
16. Technical recommendations on general occupational hygiene Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.
17. Technical recommendations to prevent environmental risks It is recommended to have absorbent material available at close proximity to the product
18. Technical measures for storage Minimum Temp.: 5 °C Maximum Temp.: 30 °C Maximum time: 6 Months General conditions for storage Avoid sources of heat, radiation, sta electricity and contact with food.
19. Respiratory protection The use of protection equipment (FFP3 Masks)will be necessary if a mist forms or if the occupational exposure limits are exceeded.
20. Mandatory Protective gloves against minor risks Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+A1:2010 and EN ISO 374-1:2016+ A1:2018
21. Mandatory face protection Panoramic glasses against splash/projections. Clean daily and disinfect periodically according to the manufacturer’s instructions. Use if there is a risk of splashing.
22. Emergency shower ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011 Eyewash stations DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
23. Code 08 04 10 Description waste adhesives and sealants other than those mentioned in 08 04 09 Waste Class Non dangerous All empty packaging to be returned to region and disposed of in Drum A

Documents Associated with this Risk Assessment : Styccobond-F48-Plus-iss-2-1.pdf(SDS) Styccobond-F48 Safety data sheet.pdf(Safety Data Sheet) Styccobond-F48 SDS.pdf(SDS)

Review Date : 10/06/2025