

HAZARDOUS SUBSTANCES RISK ASSESSMENT

Designer Contracts Ltd

Unit 8, Church View, Coney Green, Chesterfield, S45 9HA

CPL Flexyfix	Date of Assessment : 15/08/2024	Reference : CPL - Flexyfix
Risk Assessor : Laura Cross	Risk Assessor :	
Other People Involved in Making This Assessment : Antony Maidens		

R or H Descriptors:	S or P Descriptors:
Additional Information	
Workspace Exposure Limit (WEL) No WEL stated on Safety Data Sheet	

Primary route(s) of entry : Absorption, Ingestion, Inhalation	
This is a Group Substance.	The quantity used per batch or work period is: Medium (1-1000kg or 1-1000L)
The Substance is a Liquid of Low volatility	
is the control measure appropriate to control the health risks from the use of this substance. Health Surveillance is not required.	

Existing Control Measures
1. Always use in well ventilated areas.
2. First aid measures: If you feel unwell, seek medical advice. After Inhalation, remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.
3. After skin contact: Rinse with water. Soap may be used. Take victim to a doctor if irritation persists. After eye contact: Rinse with water. Take victim to an ophthalmologist if irritation persists After ingestion: Rinse mouth with water. Consult a doctor/medical service if you feel unwell.
4. Suitable extinguishing media: Adapt extinguishing media to the environment. Unsuitable extinguishing media None. Special exposure hazards Upon combustion: formation of CO, CO2 and small quantities of nitrous vapours, hydrogen chloride.
5. No specific fire fighting instructions required. Special protective equipment for firefighters: Gloves. Protective clothing. Heat/fire exposure: compressed air/oxygen apparatus
6. Environmental precautions: Contain leaking substance. Use appropriate containment to avoid environmental contamination..
7. Safe storage requirements: Store in a dry area. Store at room temperature. Meet the legal requirements. Max. storage time: 2 year(s).
8. Observe normal hygiene standards. Keep container tightly closed. Do not eat, drink or smoke during work.
9. Gloves to be worn whilst using product.
10. Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC). 08 04 10 (wastes from MFSU of adhesives and sealants (including waterproofing products): waste adhesives and sealants other than those mentioned in 08 04 09). All empty packaging to be returned to region and disposed of in Drum A

Documents Associated with this Risk Assessment : Flexyfix-SDS-Rev-304.pdf(SDS)

Review Date : 02/09/2025