

## HAZARDOUS SUBSTANCES RISK ASSESSMENT

### Designer Contracts Ltd

Unit 8, Church View, Coney Green, Chesterfield, S45 9HA

<b>CPL - Styccobond F44</b>	<b>Date of Assessment :</b> 06/03/2025	<b>Reference :</b> CPL - Styccobond F44
<b>Risk Assessor :</b> Laura Cross	<b>Risk Assessor :</b>	
<b>Other People Involved in Making This Assessment :</b> Antony Maidens		

<b>R or H Descriptors:</b>	<b>S or P Descriptors:</b>
<b>Additional Information</b>	
<b>Workspace Exposure Limit (WEL)</b> No WEL stated on Safety Data Sheet	

<b>Primary route(s) of entry :</b> Absorption, Ingestion, Inhalation	
<b>This is a Group Substance.</b>	<b>The quantity used per batch or work period is:</b> Medium (1-1000kg or 1-1000L)
<b>The Substance is a Liquid of Low volatility</b>	
<b>is the control measure appropriate to control the health risks from the use of this substance. Health Surveillance is not required.</b>	

<b>Existing Control Measures</b>
1. Description of first aid measures: Consult a doctor in case of discomfort showing the SDS for the product. By inhalation: In case of symptoms, move the person affected into fresh air.
2. Personal precautions Wear protective gloves, eye and face protection
3. By ingestion/aspiration: In case of consumption in large quantities, it is recommended to seek medical assistance.
4. Methods for cleaning up Contain and absorb spillage with sand, earth or other non-combustible material. Collect and place in suitable waste disposal containers and seal securely.
5. A.- Specific storage requirements Minimum Temp.: 5 °C Maximum Temp.: 30 °C Technical recommendations on general occupational hygiene Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.
6. Exposure controls: ALWAYS USE IN A WELL VENTILATED AREA Respiratory protection The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.
7. Specific protection for the hands Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+A1:2010 and EN ISO 374-1:2016+ A1:2018
8. Panoramic glasses against splash/projections. Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing
9. Waste treatment methods: Code Description Waste class 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09 Non dangerous Dispose of empty containers in Regions Drum A

**Documents Associated with this Risk Assessment :** Styccobond-F44-iss-19.pdf(Safety Data Sheet) Re\_ Waste drum for FBall - F44.msg(Waste Drum) Styccobond F44 - SDS.pdf(Safet Data Sheet) STYCCOBOND-F44-iss-20-UK.pdf(safety data sheet) STYCCOBOND-F44-iss-21.pdf(Safety Data SHEet)

**Review Date :** 31/03/2026