

HAZARDOUS SUBSTANCES RISK ASSESSMENT

Designer Contracts Ltd

Unit 8, Church View, Coney Green, Chesterfield, S45 9HA

CPL Styccobond F41	Date of Assessment : 05/06/2025	Reference : CPL - Styccobond F41
Risk Assessor : Laura Cross	Risk Assessor :	
Other People Involved in Making This Assessment : Antony Maidens		



R or H Descriptors:	S or P Descriptors:
H301 Toxic if swallowed H310 Fatal in contact with skin H314 Causes severe skin burns and eye damage H317 May cause an allergic skin reaction H330 Fatal if inhaled H400 Very toxic to aquatic life H410 Very toxic to aquatic life with long lasting effects	
Additional Information	
Workspace Exposure Limit (WEL)	
No WEL stated on SDS	

Primary route(s) of entry : Absorption, Ingestion, Inhalation	
This is a Group D Substance.	The quantity used per batch or work period is: Medium (1-1000kg or 1-1000L)
The Substance is a Liquid of Low volatility	
Containment is the control measure appropriate to control the health risks from the use of this substance. Health Surveillance is not required.	

Existing Control Measures
1. Always use in a well ventilated area.
2. Description of first aid measures: The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

3. By inhalation: This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.
4. By skin contact: This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or if necessary shower the affected person thoroughly with cold water and neutral soap.
5. By eye contact: Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes,
6. in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.
7. By ingestion/aspiration: Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.
8. Suitable extinguishing media: Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder),
9. Unsuitable extinguishing media: Non-applicable
10. ACCIDENTAL RELEASE MEASURES; For non-emergency personnel: Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product
11. Evacuate the area and keep out those who do not have protection.
12. Environmental precautions: Avoid spillage into the aquatic environment as it contains substances potentially dangerous for this
13. Contain the product absorbed in hermetically sealed containers. In the case of serious spillage into the aquatic environment notify the relevant authority
14. Methods and material for containment and cleaning up: It is recommended: Sweep up and shovel product or collect by other means and place in container for reuse (preferred) or disposal
15. Precautions for safe handling: Technical recommendations on general occupational hygiene Do not eat or drink during the process, washing hands afterwards with suitable cleaning products
16. Technical recommendations to prevent environmental risks It is recommended to have absorbent material available at close proximity to the product
17. Specific storage requirements Minimum Temp.: 5 °C Maximum Temp.: 30 °C
18. General conditions for storage Avoid sources of heat, radiation, static electricity and contact with food.
19. EXPOSURE CONTROLS; Respiratory protection The use of protection equipment (FFP3 Masks) will be necessary if a mist forms or if the occupational exposure limits are exceeded
20. Mandatory hand protection Protective gloves against minor risks Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials,
21. Mandatory face protection Panoramic glasses against splash/projections. Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.
22. Waste treatment methods: Code - 08 04 10 Description - waste adhesives and sealants other than those mentioned in 08 04 09 Waste Class - Non dangerous All empty packaging to be returned to region and disposed of in Drum A

Documents Associated with this Risk Assessment : Styccobond-F41-iss-19.pdf(Safety Data sheet) CPL - Styccobond F41.pdf(SDS) Styccobond-F41 SDS V21.pdf(Safety Data Sheet)

Review Date : 23/06/2026