# Designer Contracts Ltd Hazardous Substances Risk Assessment

Title	CPL - Styccobond F60	Date Of Assessment	Thu 05 Jun 2025
Site	Designer Contracts Ltd	Location	All Sites
Risk Assessor	Laura Cross	Assisted by	Antony Maidens
Non-Employees Involved	-		
Review date	Wed 10 Jun 2026	Reviewer	Laura Cross

#### Substance

Substance Name	Styccobond F60	
Supplier	F. Ball and Co. Ltd.	
Date of Safety Data Sheet (SDS)	Tue 09 Jul 2024	
Details of Use	Adhesive for floors. For professional users only.	
Are there any hazard symbols on the SDS?	Yes	
Associated hazards	Hazard	
	<b>!</b> Caution	
	Longer term health hazards	
	Hazardous to the aquatic environment	

	T lammable	
Hazard Codes & Statements	Code	Description
	H411	Toxic to aquatic life with long lasting effects
	H319	Causes serious eye irritation
	H225	Highly flammable liquid and vapour
	H361	Suspected of damaging fertility or the unborn child <state effect="" if="" known="" specific=""> <state cause="" conclusively="" exposure="" hazard="" if="" is="" it="" no="" of="" other="" proven="" route="" routes="" that="" the=""></state></state>
	H315	Causes skin irritation
	H317	May cause an allergic skin reaction
	H373	cause damage to organs through prolonged or repeated exposure.
	H336	May cause drowsiness or dizziness
Precaution Codes & Statements	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
	P260	P260: Do not breathe vapours
	P273	Avoid release to the environment
	P280	Wear protective gloves/protective clothing/eye protection.
	P303 + P361 + P353	Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
	P304+ P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing
	P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

	P313	Get medical advice/attention
Does this substance have workplace exposure limits?	Yes	
Short term	1500 ppm 3620 mg/m³	
Long term	500 ppm 1210 mg/m³	
Is Health Surveillance required?	No	
Routes of entry into body	Absorption (through skin/eyes), Ingestion (swallowing), Inhalation (breathing in)	

#### <u>Assessment</u>

How much is being used per batch?	Medium (1-1000KG or 1-1000L)	
Is the substance use a solid or liquid?	Liquid	
How volatile is the liquid?	Low	
Hazard group	D	
Control system	Engineering Controls	

# Hazardous substances control system

Control Measure	Further Details
-----------------	-----------------

### **Control measures**

Existing Control Measures	Description	
	Description of first aid measures:  The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.	

Existing Control Measures	Description	
	By inhalation: Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply,etc.) requiring immediate medical assistance.	
	By skin contact: Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.	
	By eye contact: Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product	
	By ingestion/aspiration:  Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. out the mouth and throat, as they may have been affected during ingestion.	
	Suitable extinguishing media: Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC) Unsuitable extinguishing media: Water jet	
	Environmental precautions: Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.	
	Methods and material for containment and cleaning up: It is recommended:	

Existing Control Measures	Description
	Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents
	A General precautions for safe use  Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.
	B Technical recommendations for the prevention of fires and explosions  Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying  inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect
	C Technical recommendations on general occupational hygiene PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in designated areas that comply with the necessary safety conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to small amounts only. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.
	D Technical recommendations to prevent environmental risks  Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.
	Conditions for safe storage, including any incompatibilities:  A Specific storage requirements  Minimum Temp.: 5 °C  Maximum Temp.: 30 °C  B General conditions for storage  Avoid sources of heat, radiation, static electricity and contact with food
	Always use in a well ventilated area Respiratory protection; Filter mask for gases and vapours Replace when there is a taste or smell of the contaminant inside the face mask. If

Existing Control Measures	Description	
	the contaminant comes with warnings it is recommended to use isolation equipment.	
	Specific protection for the hands: Chemical protective gloves (Material: Linear low -density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm) Replace the gloves at any sign of deterioration.	
	Eye and face protection; Face shield Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.	
	Waste treatment methods; Code -08 04 09* Description - waste adhesives and sealants containing organic solvents or other hazardous substances Waste Class - Hazardous	
	All empty packaging must be returned to regions and disposed of in Drum A	

## Past reviews

Review date	Reviewer	Comments
-------------	----------	----------

### **Attachments**

Styccobond-F60 SDS V24.pdf - Thu 05 Jun 2025