

Designer Contracts Ltd

Reference:CPL – Stopgap 1200 (Fball) Part A Powder

Hazardous Substances Risk Assessment

Title	CPL – Stopgap 1200 (Fball) Part A Powder	Date Of Assessment	Wed 29 Apr 2026
Site	Designer Contracts Ltd	Location	All Sites
Risk Assessor	Laura Cross	Assisted by	Antony Maidens
Non-Employees Involved	–		
Review date	Thu 10 Jun 2027	Reviewer	Laura Cross

Substance

Substance Name	Stopgap 1200 (Fball) Part A Powder	
Supplier	F. Ball and Co. Ltd.	
Date of Safety Data Sheet (SDS)	Thu 06 Jun 2024	
Details of Use	Cementitious coating. For professional users only	
Are there any hazard symbols on the SDS?	Yes	
Associated hazards	Hazard	
	 Caution	
Hazard Codes & Statements	Code	Description
	H319	Causes serious eye irritation

Precaution Codes & Statements	H317	May cause an allergic skin reaction
	P261	Avoid breathing dust
	P280	Wear protective gloves/protective clothing/eye protection.
	P302+P352	IF ON SKIN: Wash with plenty of soap and water.
	P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P308+ P313	IF exposed or concerned: Get medical advice/ attention
	P501	Dispose of contents/ container in accordance with local/regional/national/international regulation.
Does this substance have workplace exposure limits?	Yes	
Short term	no short term on sds	
Long term	Wel (8h) 4 mg/m ³	
Is Health Surveillance required?	No	
Routes of entry into body	Absorption (through skin/eyes), Ingestion (swallowing), Inhalation (breathing in)	

Assessment

How much is being used per batch?	Medium (1–1000KG or 1–1000L)	
Is the substance use a solid or liquid?	Solid	
How dusty is the solid?	High	
Hazard group	C	
Control system	Engineering Controls	

Hazardous substances control system

Control Measure		Further Details
-----------------	--	-----------------

Control measures

Existing Control Measures	Description
	Description of first aid measures: The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort,
	By inhalation: This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest.
	By skin contact: May cause an allergic skin reaction. In case of contact it is recommended to clean the affected area thoroughly with water and neutral soap. In case of changes on the skin (stinging, redness, rashes, blisters,...), seek medical advice with this Safety Data Sheet
	By eye contact: Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product
	By ingestion/aspiration: Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.
	Suitable extinguishing media: Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems. Unsuitable extinguishing media: Non-applicable

Existing Control Measures	Description
	Personal precautions, protective equipment and emergency procedures: For non-emergency personnel: Sweep up and shovel product or collect by other means and place in container for reuse (preferred) or disposal
	Environmental precautions: This product is not classified as hazardous to the environment. Keep product away from drains, surface and ground water. Methods and material for containment and cleaning up: It is recommended: Sweep up and shovel product or collect by other means and place in container for reuse (preferred) or disposal
	Technical recommendations on general occupational hygiene Do not eat or drink during the process, washing hands afterwards with suitable cleaning products. Technical recommendations to prevent environmental risks It is recommended to have absorbent material available at close proximity to the product
	Conditions for safe storage, including any incompatibilities: A.- Specific storage requirements Minimum Temp.: 5 °C Maximum Temp.: 30 °C B.- General conditions for storage Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5 Keep the container tightly sealed and protected from open air and humidity.
	Always use in a well ventilated area, Respiratory protection Filter mask for particles Replace when an increase in resistance to breathing is observed.
	Specific protection for the hands Chemical protective gloves Replace the gloves at any sign of deterioration. Eye and face protection Panoramic glasses against splash/projections. Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.
	Waste treatment methods Code - 16 03 03* Description - inorganic wastes containing hazardous substances Waste Class - Non-hazardous

Existing Control Measures	Description
	Product – Unused residue or dry spillage: 10 13 06
	Product – after addition of water, hardened: 10 13 14, 17 01 01
	All packaging to be returned to regions and disposed of in Drum B

Past reviews

Review date	Reviewer	Comments
Tue 09 Jun 2026	Laura Cross	same sds, no changes

Attachments

Stopgap-1200-Powder-iss-9.pdf – Wed 04 Jun 2025