

Designer Contracts Ltd

Hazardous Substances Risk Assessment

Title	CPL – STYCCOBOND F48 PLUS	Date Of Assessment	Wed 29 Apr 2026
Site	Designer Contracts Ltd	Location	All Sites
Risk Assessor	Laura Cross	Assisted by	Antony Maidens
Non-Employees Involved	–		
Review date	Thu 10 Jun 2027	Reviewer	Laura Cross

Substance

Substance Name	STYCCOBOND F48 PLUS	
Supplier	F. Ball and Co. Ltd.	
Date of Safety Data Sheet (SDS)	Tue 06 Jun 2023	
Details of Use	Adhesive. For professional users only.	
Are there any hazard symbols on the SDS?	No	
Hazard Codes & Statements	Code	Description
Does this substance have workplace exposure limits?	No	
Is Health Surveillance required?	No	
Routes of entry into body	Absorption (through skin/eyes), Ingestion (swallowing), Inhalation (breathing in)	

Assessment

How much is being used per batch?	Medium (1–1000KG or 1–1000L)
Is the substance use a solid or liquid?	Liquid
How volatile is the liquid?	Low
Hazard group	N/A
Control system	N/A

Hazardous substances control system

Control Measure	Further Details
-----------------	-----------------

Control measures

Existing Control Measures	Description
	Description of first aid measures: The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.
	By inhalation: This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.
	By skin contact: This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or if necessary shower the affected person thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.
	By eye contact: Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

Existing Control Measures	Description
	By ingestion/aspiration: Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.
	Suitable extinguishing media: Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems. Unsuitable extinguishing media: Non-applicable
	Environmental precautions: It is recommended to avoid environmental spillage of both the product and its container. Methods and material for containment and cleaning up: It is recommended: Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents.
	A – General precautions for safe use Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods
	B.- Technical recommendations for the prevention of fires and explosions Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.
	C.- Technical recommendations on general occupational hygiene Do not eat or drink during the process, washing hands afterwards with suitable cleaning products. D.- Technical recommendations to prevent environmental risks It is recommended to have absorbent material available at close proximity to the product
	Conditions for safe storage, including any incompatibilities: A.- Specific storage requirements Minimum Temp.: 5 °C

Existing Control Measures	Description
	Maximum Temp.: 30 °C B.- General conditions for storage Avoid sources of heat, radiation, static electricity and contact with food
	Always use in a well ventilated area. B.- Respiratory protection The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded Specific protection for the hands – Protective gloves against minor risks Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN ISO 21420:2020 and EN ISO 374-1:2016+ A1:2018
	Eye and face protection; Panoramic glasses against splash/projections. Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.
	Waste treatment methods: Code 08 04 10. Description – waste adhesives and sealants other than those mentioned in 08 04 09. Waste Class – Non-hazardous.
	Waste management (disposal and evaluation): Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste (England & Wales) Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains
	All empty packaging must be returned to region and disposed of in Drum B.

Past reviews

Review date	Reviewer	Comments
Wed 10 Jun 2026	Laura Cross	same sds no changes

Attachments

Styccobond-F48 SDS v4.pdf - Thu 05 Jun 2025