

Designer Contracts Ltd

Hazardous Substances Risk Assessment

Reference:CPL-S

Title	CPL - Styccobond F41	Date Of Assessment	Tue 21 Jul 2026
Site	Designer Contracts Ltd	Location	All Sites
Risk Assessor	Laura Cross	Assisted by	Antony Maidens
Non-Employees Involved	–		
Review date	Thu 24 Jun 2027	Reviewer	Laura Cross

Substance

Substance Name	Styccobond F41
Supplier	F. Ball and Co. Ltd
Date of Safety Data Sheet (SDS)	Tue 06 Jun 2023
Details of Use	Adhesive. For professional users only
Are there any hazard symbols on the SDS?	Yes
Associated hazards	Hazard
	 Acute toxicity
	 Corrosive
	 Hazardous to the aquatic environment

Hazard Codes & Statements	Code	Description
	EUH 208	May produce an allergic reaction
	EUH 210	Safety data sheet available on request
	H310 + H330	Fatal in contact with skin or if inhaled
	H400	Very toxic to aquatic life
	H410	Very toxic to aquatic life with long lasting effects
	H314	Causes severe skin burns and eye damage
	H317	May cause an allergic skin reaction
Precaution Codes & Statements	P102	Keep out of reach of children
Does this substance have workplace exposure limits?	No	
Is Health Surveillance required?	No	
Routes of entry into body	Absorption (through skin/eyes), Ingestion (swallowing), Inhalation (breathing in)	

Assessment

How much is being used per batch?	Medium (1-1000KG or 1-1000L)
Is the substance use a solid or liquid?	Liquid
How volatile is the liquid?	Low
Hazard group	D
Control system	Engineering Controls

Hazardous substances control system

Control Measure	Further Details
-----------------	-----------------

Control measures

Existing Control Measures	Description
	Description of first aid measures: The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.
	By inhalation: This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.
	By skin contact: This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or if necessary shower the affected person thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.
	By eye contact: Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.
	By ingestion/aspiration: Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.
	Suitable extinguishing media: Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.
	Unsuitable extinguishing media: Non-applicable

Existing Control Measures	Description
	Special hazards arising from the substance or mixture: As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.
	Environmental precautions: It is recommended to avoid environmental spillage of both the product and its container. Methods and material for containment and cleaning up: It is recommended: Sweep up and shovel product or collect by other means and place in container for reuse (preferred) or disposal
	Technical recommendations on general occupational hygiene Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.
	Technical recommendations to prevent environmental risks It is recommended to have absorbent material available at close proximity to the product
	Conditions for safe storage, including any incompatibilities: A.- Specific storage requirements Minimum Temp.: 5 °C Maximum Temp.: 30 °C B.- General conditions for storage Avoid sources of heat, radiation, static electricity and contact with food.
	All empty FBall yellow tubs to be returned to region for recycling at designer contracts central distribution centre.

Past reviews

Review date	Reviewer	Comments
Wed 23 Jun 2027	Laura Cross	MSDS added
Wed 23 Jun 2027	Laura Cross	updated empty packaging details

Attachments

CPL – Styccobond F41 – Safety Data Sheet.pdf – Fri 05 Jun 2026